


Technical Datasheet

**Description:** Contour Copper Hand Waxed Switched Fused Spur (White Insert/Polished Chrome Switch)

**Part Number:** CBCHX257



Information

|                         |                                                                                                                                                           |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Dimensions (mm)         | 85 (W) x 85 (H) x 8 (D)                                                                                                                                   |
| Insert Material         | Polycarbonate                                                                                                                                             |
| Earth Strap             | Mild Steel                                                                                                                                                |
| Operating Voltage(AC)   | 250V @ 50Hz                                                                                                                                               |
| Termination Type        | Screw                                                                                                                                                     |
| Warranty                | 10 years                                                                                                                                                  |
| Product Class 1         | Must be earthed                                                                                                                                           |
| Maintenance             | Clean with a soft cloth only. Do not use a cleaning agent of any description.                                                                             |
| Style                   | Rounded Profile                                                                                                                                           |
| Switch Material         | Metal                                                                                                                                                     |
| Required back box depth | 25mm                                                                                                                                                      |
| Load Rating             | 13A                                                                                                                                                       |
| Switch type             | Double pole                                                                                                                                               |
| Terminal Capacity       | 3x 2.5mm <sup>2</sup> ,3x 4.0mm <sup>2</sup> , 2x 6.0mm <sup>2</sup> (L&N) / 3x 2.5mm <sup>2</sup> ,2x 4.0mm <sup>2</sup> , 1x 6.0mm <sup>2</sup> (EARTH) |
| Standards               | BS 1363                                                                                                                                                   |
| IP Rating               | IP2XD                                                                                                                                                     |