



**Description:** Contour Copper Light Switch (4 Gang/Black Switch)

**Part Number:** CBC4B



# Information

|                         |                                                                                                 |
|-------------------------|-------------------------------------------------------------------------------------------------|
| Dimensions (mm)         | 146 (W) x 85 (H) x 8 (D)                                                                        |
| Insert Material         | Polycarbonate                                                                                   |
| Earth Strap             | Mild Steel                                                                                      |
| Operating Voltage(AC)   | 250V @ 50Hz                                                                                     |
| Termination Type        | Screw                                                                                           |
| Warranty                | 10 years                                                                                        |
| Product Class 1         | Must be earthed                                                                                 |
| Maintenance             | Clean with a soft cloth only. Do not use a cleaning agent of any description.                   |
| Style                   | Rounded Profile                                                                                 |
| Plate Base Material     | Copper                                                                                          |
| Switch Material         | Polycarbonate                                                                                   |
| Required back box depth | 16mm                                                                                            |
| Load Rating             | 10A                                                                                             |
| Switch type             | Single pole, 2 way                                                                              |
| Terminal Capacity       | 4 x 1.0mm <sup>2</sup> , 4 x 1.5mm <sup>2</sup> ,2 x 2.5mm <sup>2</sup> ,1 x 4.0mm <sup>2</sup> |
| Standards               | BS EN 60669-1                                                                                   |
| IP Rating               | IP2XD                                                                                           |