



**Description:** Victorian Satin Nickel Shaver Socket (Black Insert)

**Part Number:** VSN30B



# Information

|                         |                                                                                                   |
|-------------------------|---------------------------------------------------------------------------------------------------|
| Dimensions (mm)         | 94 (W) x 156 (H) x 9 (D)                                                                          |
| Insert Material         | Polycarbonate                                                                                     |
| Earth Strap             | Mild Steel                                                                                        |
| Operating Voltage(AC)   | 250V @ 50Hz                                                                                       |
| Termination Type        | Screw                                                                                             |
| Warranty                | 10 years                                                                                          |
| Product Class 1         | Must be earthed                                                                                   |
| Maintenance             | Clean with a soft cloth only. Do not use a cleaning agent of any description.                     |
| Style                   | Multi Stepped Profile                                                                             |
| Plate Base Material     | Solid Brass                                                                                       |
| Required back box depth | 47mm                                                                                              |
| Load Rating             | 20W                                                                                               |
| Terminal Capacity       | 4 x 1.0mm <sup>2</sup> , 4 x 1.5mm <sup>2</sup> , 2 x 2.5mm <sup>2</sup> , 1 x 4.0mm <sup>2</sup> |
| Standards               | BS EN 61558                                                                                       |
| IP Rating               | IP21D                                                                                             |