

## Technical Datasheet

**Description:** Flat Verdigris Switched Fused Spur with Flex Outlet (Black Switch)

**Part Number:** FV56B



## Information

|                                |   |
|--------------------------------|---|
| <b>Plate Dimensions (mm)</b>   | 86 (W) x 86 (H) x 2 (D)   |
| <b>Insert Material</b>         | Polycarbonate   |
| <b>Earth Strap</b>             | Mild Steel  |
| <b>Operating Voltage(AC)</b>   | 250V @ 50Hz   |
| <b>Termination Type</b>        | Screw   |
| <b>Warranty</b>                | 10 years  |
| <b>Product Class 1</b>         | Must be earthed   |
| <b>Maintenance</b>             | Clean with a soft cloth only. Do not use a cleaning agent of any description.   |
| <b>Please Note</b>             | Do not use masking tape on this product.  |
| <b>Style</b>                   | Flat Profile  |
| <b>Switch Material</b>         | Polycarbonate   |
| <b>Required back box depth</b> | 35mm  |
| <b>Load Rating</b>             | 13A   |
| <b>Switch type</b>             | Double pole   |
| <b>Terminal Capacity</b>       | 3x 2.5mm <sup>2</sup> , 3x 4.0mm <sup>2</sup> , 2x 6.0mm <sup>2</sup> (L&N) / 3x 2.5mm <sup>2</sup> , 2x 4.0mm <sup>2</sup> , 1x 6.0mm <sup>2</sup> (EARTH) |
| <b>Standards</b>               | BS 1363   |
| <b>IP Rating</b>               | IP2XD   |