

## Technical Datasheet

**Description:** Monarch Satin Nickel 45A DP Switch with Neon (White Insert/Red Switch/Vertical Plate)

**Part Number:** MSN28W



## Information

|                                |  |
|--------------------------------|--|
| <b>Plate Dimensions (mm)</b>   | 94 (W) x 154 (H) x 8 (D)   |
| <b>Insert Material</b>         | Polycarbonate  |
| <b>Earth Strap</b>             | Mild Steel   |
| <b>Operating Voltage(AC)</b>   | 250V @ 50Hz  |
| <b>Termination Type</b>        | Screw  |
| <b>Warranty</b>                | 10 years   |
| <b>Product Class 1</b>         | Must be earthed  |
| <b>Maintenance</b>             | Clean with a soft cloth only. Do not use a cleaning agent of any description.  |
| <b>Please Note</b>             | Do not use masking tape on this product.   |
| <b>Style</b>                   | Stepped Profile with Rope edge   |
| <b>Plate Material</b>          | Nickel Plated Solid Brass, Hand-finished, Lacquered  |
| <b>Switch Material</b>         | Metal  |
| <b>Required back box depth</b> | 47mm   |
| <b>Load Rating</b>             | 45A  |
| <b>Switch type</b>             | Double pole  |
| <b>Terminal Capacity</b>       | 4x 4.0mm <sup>2</sup> , 3x 6.0mm <sup>2</sup> , 1x 16.0mm <sup>2</sup> (L&N) / 3x 2.5mm <sup>2</sup> , 2x 4.0mm <sup>2</sup> , 1x 6.0mm <sup>2</sup> (EARTH) |
| <b>Standards</b>               | BS EN 60669-1, BS 4177(sockets)  |
| <b>IP Rating</b>               | IP2XD  |